


A Total Dedication to New Technological Level




### Feature

- Main structure of the CNC cylindrical grinder, when in combination with angle control of spindle by C axis, is capable of grinding various special shaped workpiece.
- Working spindle carried with precision angle decoder, high resolution of angle control reaching up to 0.1um.
- The feed axis is equipped with close loop control optical scale to reach high precision.
- Retaining various functions of CNC cylindrical grinder, and applicable to angle and speed control.
- Fast and easy transferring custom-made grinding program, when operated with PALMARY-developed CAD/CAM software.
- A high-speed algorithm controller executed under PC Based + Windows XP, allowing input of 3rd-party software.
- An optional sound frequency anti-crashproof system, consistent grinding operations are ensured. Another benefit is to prevent parts colliding caused by erroneous motion when executing programs.
- Uni-point dressing device or roller type dressing device is equipped according to functional requirement.
- USB access, combined with the market available USB high-speed transmission interface, providing excellent data portability.
- with 1ms single session processing time.




#### Wheel Spindle with Hydro-static Bearing Absolutely No Metal-to-Metal Contact

Hybrid Palmary hydro-static Bearings are used for the wheel spindle bearings. Metal-to-metal contact will never occur with these highly rigid bearings which have a damping effect and make 0.5um the new definition of wheel spindle rotational accuracy.




#### Tailstock Lubrication System Simplifies Maintenance

An automatic oil bath lubrication system has been provided for the tailstock to maintain high-level accuracy. An oil level gauge enables quick and sure oil level checks.



#### Special hydro-static Bearing

The wheel spindle runs by using a special hydro-static bearing and is especially ideal for precision grinding work. It feature high speed, no friction between metals, no heat generation, deformation-free, extra high accuracy and continual use.



#### Advanced Hydro-static Lubrication System

The slideways of the table and of the wheel head are lubricated by an advanced automatic hydro-static lubrication system. This provides various features such as extremely smooth movement, added feeding accuracy and superior grinding accuracy.



Fargor 8070 High Speed Controller




- Diamond roller dressing device
- Semi-Auto. Grinding Wheel Balance

### Standard Accessories

Optical Scale ( For X Axis & C Axis )	Tool and kit x 1Set	Hydraulic Tank with Oil Cooler x 1Set
Grinding Wheel and Grinding Wheel Flange x 1Set	Carbide Tipped Work Centers x 2 Set	Work Lamp x 1 Set
Diamond Tool Holder ( Table Mounted Type ) x 1Set	Coolant Equipment x 1Set	

### Optional Accessories

Cam Locked Driving Dogs	Magnetic Coolant Separator	Cap Control	Diamond roller dressing device
Work Holder ( 2 pcs /set )	Magnetic and Paper Filter	Semi-Auto. Grinding Wheel Balancer	CBN Wheel
2-point Steady Rest	Automatic Grinding Wheel Balancer	Oil Mist Collector	CAD / CAM Software
Adjustable 3-point Steady Rest	Wheel Balancing Stand and Arbor	Fully Enclosed Splash Guard	
Adjustable 3-jaw Scroll Chuck	Touch probe Gauge	Spare Grinding Wheel and Grinding Wheel Flange	
Adjustable 4-jaw Chuck	Auto In-process Gauge	Hydraulic Tailstock	



### OCD-3260 CAM

Model	OCD-3240CAM	OCD-3260CAM	OCD-32100CAM	
Swing Over Table		ø 320 mm		
Distance Between Centers	400 mm	600 mm	1000 mm	
Max. Grinding Diameter		ø 300 mm		
Max. Load Held Between Centers		150 kg		
Wheel	OD x Width x ID	ø 355 x 50 x ø127 mm		
	Linear Velocity	30 m/s		
	Speed	1783 RPM (1940 R.P.M. )		
Wheel head	Rapid Feedrate	10 m/min		
	Min. Input Increment	0.001 mm ( 0.0001 mm )		
	Rapid Feedrate	10 m/min		
Table	Min. Input Increment	0.001 mm ( 0.0001 mm )		
	Swiveling Angle	0° ~ 12°	0° ~ 12°	0° ~ 10°
	Swiveling Angle	-30° ~ +90° deg		
Workhead	Center	MT. No. 4		
	Speed	10-500 R.P.M.		
	Cam Grinding Speed	0-30 R.P.M.		
	Max. Load of Spindle ( tool holder included)	35 kg ( Max. Length : 150 mm )		
Tailstock	Center	MT. No.4		
	Stroke	25 mm		
Drive Motors	Wheel Spindle	3.7 ( 4P ) kw		
	Work Spindle ( AC Servo motor )	0.8 kw	0.8kw	1.3kw
	Wheel Head Feed	1.2 kw ( AC Servo motor )		
	Table Feed	1.8 kw ( AC Servo motor )		
	Hydraulic Pump	0.75 ( 6P ) kw		
	Wheel Spindle Lubricant	0.18 ( 2P ) kw		
	Coolant Pump	0.18 ( 4P ) kw		
Tank Capacities	Wheel Spindle Bearing Lubricant	12 L		
	Lubrication Oil Tank	60 L		
Machine Weight	3400kg	4250 kg	5300 kg	



#### PALMARY MACHINERY CO., LTD. (TAIWAN)

No.77, Gongye Rd., Dali City, Taichung County 412, Taiwan.  
T. +886-4-2492-9799 F. +886-4-2492-9499  
palmary@grinding.com.tw

#### SHANGYU DAI KING SEIKI CO., LTD. (CHINA)

No.288, Yongxiang Road, Economic Development Zone,  
Shangyu City, Zhejiang province 312300, China.  
T. +86-575-82186081~3 F. +86-575-82186085  
daikingseiki@yahoo.com.cn

#### PALMARY MACHINERY CO., LTD. (THAILAND)

200 Moo 1 Khaerai, Kratumbar,  
Samutsakorn Thailand, 74110.  
T. +66-34-476225~6 F. +66-34-849516  
thailand@grinding.com.tw

[www.palmary.com.tw](http://www.palmary.com.tw)

[www.grinding.com.tw](http://www.grinding.com.tw)



## CNC CYLINDRICAL GRINDER CAM GRINDING

